STANDARDS PRESENTATION TO

Attachment No. 1 Page 1 of 1

CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD

PROPOSED STATE STANDARD, TITLE 8, CHAPTER 4

Amend Section 4889 to read as follows:

§4889. Warning Devices.

(a) An audible warning device shall be mounted on each <u>overhead traveling or bridge</u> crane, eontrolled from a cage or cab, equipped with a power traveling mechanism, to warn persons in or <u>near the path of crane travel</u>.

EXCEPTION: Floor operated cranes whose movements are controlled by an operator through the use of controllers contained in a pendant station suspended from the crane.

(b) When starting the bridge and when the load or hook approaches personnel, the warning signal shall be sounded.

EXCEPTION: When an employee whose specific duties are to spot and direct crane operations who is in contact with the operator by signals, telephone, radio, etc.

- (c) Cranes traveling on rails or rubber tires at ground level and operating in work areas shall be equipped with automatic warning devices to warn employees whenever the crane is traveling.
- (d) Cranes controlled from a cage or cab equipped with a power traveling mechanism whose warning device has become inoperative shall not be operated until the warning device is repaired or replaced. Temporary crane operation will be permitted if a person spotter is positioned having a clear view of the crane load and operator is present whose sole specific duty is to warn those in the path of the crane or its load.

NOTE: Authority cited: Section 142.3, Labor Code. Reference: Section 142.3, Labor Code.